

Heavy Duty Products, IEC Pin and Sleeve
Devices, Female, Receptacle, 60A 3-Phase
Delta 250V AC, 3-Pole 4-Wire Grounding,
Terminal Screws, Low Profile

By Hubbell Wiring Device-Kellems
Catalog # [A460R9](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Female,
Receptacle, 60A 3-Phase Delta 250V AC, 3-Pole 4-Wire
Grounding, Terminal Screws, Blue, Low Profile

Features

- Split sleeves with self-adjusting stainless steel springs
- Color coding for easy identification of mating devices
- Stainless steel terminal screws resist rust and corrosion

Application

High Ampacity Watertight Connections

Performance

Electrical - Current Interrupting - Certified for current interruption at full rated current, Electrical - Dielectric Voltage - Withstands 3,000V AC, Electrical - Max Working Voltage - 250V RMS, Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17, Environmental - Ingress Protection - IP22 Suitability, Environmental - Operating Temperatures - Max. Continuous +75°C, Min. -40°C w/o impact, Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682, Mechanical - Product Identification - Ratings are a permanent part of the device housing, Mechanical - Terminal Identification - Terminals identified in accordance with North American convention

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA

Conductor

Number Of Wires	4-Wire
Wire Size	#8 AWG to #2 AWG
Number Of Poles	3-Pole

Current

Ampereage Rating	60 A
Voltage Rating Description	3 Phase 250 VAC



Current Rating	60 A
Voltage Rating	3 Phase 250 VAC
Wattage	15000
Connectivity	Pressure Terminal Screws
Phase	Three Phase
Current / Amperage Rating	60 A

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color	Blue
Style	Standard Service
Series	Low Profile
Specifications	• Assembly Screws - Stainless Steel • Assembly Screws - Stainless Steel • Body - Zytel® 101 Nylon • Sleeves - Brass CDA #360 • Terminal Screws - Stainless Steel
UPC	783585507859
Type	IP22 Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Single-Low Profile
Material	Thermoplastic

Logistics

Pallet Quantity	250
Carton Quantity	10

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)