

Kellems Wire Management, Liquidtight
System, PolyTuff® II Non-Metallic Tubing, 1",
100 feet, Black

By Hubbell Wiring Device-Kellems
Catalog # [B2100](#)

Kellems Wire Management, Liquidtight System, PolyTuff® II Non-
Metallic Tubing, 1", 100 feet, Black

Features

- PVC core with corrugated walls bonded to PVC jacket
- Non-metallic construction ends metal fatigue and separation problems
- Handles twists, turns, bends, switchbacks and straightaways with ease

Application

UL1660

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Yes
Industry Standard(s)	• CSA Certified • UL Recognized

Current

Voltage Rating	300 V
----------------	-------

Dimensions

Length	100 ft
Trade Size	1
Width	1.30 in



Force Related

Load Capacity	Extra Flexible
---------------	----------------

General

Color	Black
Specifications	• Bend Radius Inches (mm) - 3.00" (76.2) • Conduit ID/OD Inches (mm) - 1.05"/1.30" (26.0/33.1) • Material - Co-extruded rigid and flexible PVC • Trade Size - 1 Inch
UPC	783585333243
Type	PolyTuff® II Liquidtight Tubing
Material	Co-extruded rigid and flexible PVC

Logistics

Pallet Quantity	2000
Carton Quantity	100

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)