

Straight Blade Devices, Receptacles,
Tamper-Resistant Duplex,
Commercial/Industrial Grade, 2-Pole 3-
Wire Grounding, 20A 125V, 5-20R, Gray,
Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [BR20GRYWRT](#)R

Straight Blade Devices, Receptacles, Tamper-Resistant Duplex,
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 20A
125V, 5-20R, Gray, Single Pack

Features

- Weather-resistance complies with national electrical code requirements
- Tamper-resistant shutter complies with national electrical code requirements
- Smooth face
- Wrap-around galvanized steel strap
- Triple wipe contacts

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #12-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Environmental Conditions	Weather Resistant
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA C22.2, No. 42 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Connectivity	Back and Side Wired
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Display Size	Standard Sized Product
Weight	0.2 lb.

General

Color	Gray
Style	Smooth Face
Series	Commercial Specification Grade
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Stainless steel • Mounting Screws - Stainless steel • Power Contacts - .030 in. (.8) Brass • Terminal Screws - Stainless steel • Wire Clamp - .062 in. (1.6) Nickel plated steell
UPC	783585144702
Type	Tamper-Resistant, Weather Resistant
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex
Material	Nylon

Logistics



Pallet Quantity	8000	Horsepower - Maximum	1
Carton Quantity	10		
Operational		Product Assets	
Operating Temperature	Maximum continuous 75°C and minimum -40°C without impact	Catalog [English]	Catalog Page [English]

