

Kellems Wire Management, Deluxe Cord Grips, Straight Male Stainless, .500"-.625", 3/4" with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [CG610SST](#)

Kellems Wire Management, Deluxe Cord Grips, Straight Male Stainless, .500"-.625", 3/4" with Mesh

Features

- Stainless Steel Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

Application

Straight Male- Form 2

Performance

Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting), Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C, Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C), Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Cable Size	.500"-.625" (1.27-1.59)
Cable Diameter Range	0.500 in-0.625 in



Conductor Range	0.5-0.625 in (1.27-1.59 mm)
-----------------	-----------------------------

Dimensions

Display Size	3/4" NPT
Thread Size	3/4" NPT

General

Style	For Insulated Cables
Series	Deluxe Cord Grips
Specifications	• Bushings - Neoprene • Fittings - Stainless Steel • NPT Thread Size - 3/4 Inch • Strand - Stainless Steel
UPC	783585338149
Type	Straight Male Thread
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Deluxe Cord Grips
Material	Stainless Steel Fittings, Stainless Steel Mesh

Logistics

Carton Quantity	5
-----------------	---

Operational

Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)