

Kellems Wire Management, Deluxe Cord Grips, Straight Male Non- Metallic, .500-.625", 1" with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [CG810NM](#)

Kellems Wire Management, Deluxe Cord Grips, Straight Male Non- Metallic, .500-.625", 1" with Mesh

Features

- Nylon Fitting
- Non-metallic mesh is corrosion resistant
- Neoprene bushing is oil and watertight

Application

Straight Male- Form 4

Performance

Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting), Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C, Environmental - Operating Temperatures - -30°F to +225°F (-34°C to +107°C), Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Cable Size	.500"-.625" (1.27-1.59)
Cable Diameter Range	0.500 in-0.625 in
Conductor Range	.500"-.625" (1.27-1.59)

Dimensions

Length	1.88 in
--------	---------



Display Size	1" NPT
Weight	0.15 lb.
Height	2.45 in
Width	1.88 in
Thread Size	1" NPT
Dimensions	1.88 in x 1.88 in x 2.45 in

General

Style	For Insulated Cables
Cord Range	.500"-.625" (1.27-1.59)
Series	Deluxe Cord Grips Series
Specifications	• Bushings - Neoprene • Fittings - Nylon • NPT Thread Size - 1 Inch • Strand - Non-metal
UPC	783585335087
Type	Straight Male Thread
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Deluxe Cord Grips
Material	Nylon Fittings, Non-Metallic Mesh

Logistics

Pallet Quantity	960
Carton Quantity	5

Operational

Temperature Rating	Minimum -30 Deg F to 225 Deg F (-34 Deg C to 107 Deg C)
--------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)