

Straight Blade Devices, Receptacles,
Duplex, Commercial Grade, 2-Pole 3-Wire
Grounding, 15A 125V, 5-15R, Ivory, Single
Pack, With 8”StrandedLeads.

By Hubbell Wiring Device-Kellems
Catalog # [CR15IP2](#)

Straight Blade Devices, Receptacles, Duplex, Commercial Grade,
2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Ivory, Single Pack,
With 8”StrandedLeads.

Features

- Fully insulated design with 8-inch stranded wire leads
- Smooth face
- Triple wipe contacts

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94V-2, Environmental - Operating Temperatures - Maximum
continuous 75°C minimum -40°C (w/o impact), Mechanical -
Product Identification - Ratings are a permanent part of the
device

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V



Wattage	1875 W
Connectivity	Side Wired
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.32 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	3.28 in
Width	0.83 in
Dimensions	1.32 in x 0.83 in x 3.28 in

General

Color	Ivory
Style	Smooth Face
Series	Commercial Specification Grade
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contact - .031 in. (.8) Brass • Lead Wires - #12 AWG THHN stranded copper wire • Mounting Screws - Galvanized steel • Mounting Strap - .040 in. (1) Galvanized steel • Power Contacts - .030 in. (.8) Brass
UPC	783585146171
Type	Pre-Wired
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex
Material	Nylon

Logistics

Carton Quantity	50
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [Spanish, French, English]



A Hubbell brand