

Straight Blade Devices, Receptacles,  
Tamper-Resistant Duplex, Commercial  
Grade, 2-Pole 3-Wire Grounding, 20A 125V,  
5-20R, White, Single Pack

By Hubbell Wiring Device-Kellems  
Catalog # [CR20WHITR](#)

Straight Blade Devices, Receptacles, Tamper-Resistant Duplex,  
Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R,  
White, Single Pack

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Smooth face
- Triple wipe contacts

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #12-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

|                                    |                                                                                                                                                              |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards - RoHS Compliance Status | CM                                                                                                                                                           |
| Environmental Conditions           | Indoor Dry Unless Protected By Additional Means                                                                                                              |
| EU RoHS Indicator                  | Yes                                                                                                                                                          |
| Nema Rating                        | 5-20R                                                                                                                                                        |
| Industry Standard(s)               | <ul style="list-style-type: none"><li>• Certified to CSA, C22.2, No. 42</li><li>• NEMA® WD-6 Compliant</li><li>• UL Listed to UL498 File No. E2186</li></ul> |

Conductor

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #12 AWG to #10 AWG |
| Number Of Poles | 2-Pole             |

Current

|                 |      |
|-----------------|------|
| Amperage Rating | 20 A |
|-----------------|------|



|                            |                           |
|----------------------------|---------------------------|
| Voltage Rating Description | 125 V                     |
| Dielectric Strength        | Withstands 2,000V minimum |
| Current Rating             | 20 A                      |
| Voltage Rating             | 125 V                     |
| Wattage                    | 2500 W                    |
| Connectivity               | Side Wired                |
| Phase                      | Single Phase              |
| Current / Amperage Rating  | 20 A                      |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 1.32 in                     |
| Display Size | Standard Sized Product      |
| Weight       | 0.15 lb.                    |
| Height       | 3.28 in                     |
| Width        | 1.14 in                     |
| Dimensions   | 1.32 in x 1.14 in x 3.28 in |

General

|                              |                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                        | White                                                                                                                                                                                                                                                                                                                                           |
| Style                        | Smooth Face                                                                                                                                                                                                                                                                                                                                     |
| Series                       | Commercial Specification Grade                                                                                                                                                                                                                                                                                                                  |
| Specifications               | <ul style="list-style-type: none"><li>• Automatic Self-grounding Staple - Stainless steel</li><li>• Base - Nylon</li><li>• Face - Nylon</li><li>• Mounting Screws - Galvanized steel</li><li>• Mounting Strap - .040 in. (1) Galvanized steel</li><li>• Power Contacts - .030 in. (.8) Brass</li><li>• Terminal Screws - Plated steel</li></ul> |
| UPC                          | 783585144306                                                                                                                                                                                                                                                                                                                                    |
| Type                         | Tamper-Resistant                                                                                                                                                                                                                                                                                                                                |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                                                                                                                                                                                  |
| Item Type                    | Traditional Duplex                                                                                                                                                                                                                                                                                                                              |
| Material                     | Nylon                                                                                                                                                                                                                                                                                                                                           |

Logistics

|                 |      |
|-----------------|------|
| Pallet Quantity | 7500 |
| Carton Quantity | 10   |

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Horsepower - Maximum  | 1                                                        |



A Hubbell brand

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)