

Locking Devices, Twist-Lock®, Industrial,
Flanged Inlet, 50A, 125V, 2-Pole 3-Wire
Grounding, Non-NEMA, Screw Terminal,
Steel

By Hubbell Wiring Device-Kellems
Catalog # [CS6377](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 50A, 125V,
2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Steel

Features

- Metallic flanged casing provides maximum strength and protection
- Thermoset interior provides superior heat resistance

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V0, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact) Mechanical - Terminal Accommodation - #10 AWG - #6 AWG solid or stranded copper wire only

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	50 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	50 A



Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	50 A

Dimensions

Length	3.50 in
Display Size	Standard Sized Product
Weight	0.80 lb.
Height	2.17 in
Width	2.62 in
Dimensions	3.50 in x 2.62 in x 2.17 in

General

Color	Metallic
Specifications	• Blades - Brass • Casing - Steel, zinc plated • Terminal Retainer - Phenolic • Terminal Screws - Steel
UPC	783585871356
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Item Type	Single Flanged Inlet
Material	Steel, Zinc Plated

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)