

Switches and Lighting Controls, Toggle
Switch, Commercial Grade, Single Pole, 15A
120/277V AC, Back and Side Wired, Brown

By Hubbell Wiring Device-Kellems
Catalog # [CSB115](#)

Switches and Lighting Controls, Toggle Switch, Commercial
Grade, Single Pole, 15A 120/277V AC, Back and Side Wired,
Brown

Features

- Thread cleaning captive mounting screw
- Abuse resistant nylon toggle
- Steel, zinc plated bridge is corrosion resistant

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum
for 1 minute, Electrical - Max. Continuous Current - 15A, Electrical
- Max. Working Voltage - 277V AC, Electrical - Overload -
Minimum 4.8 times rated current for 100 cycles, Electrical -
Temperature Rise - 30°C maximum at rated current,
Environmental - Flammability - UL 94V-2, Environmental -
Operating Temperature - Max. continuous: 75°C, Min. continuous:
-40°C without impact, Mechanical - Terminal Accommodations -
#14 AWG min. - #10 AWG max. solid and stranded copper wire
only

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Single Pole

Current

Amperage Rating	15 A
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A

Dimensions

Length	4.18 in
Weight	0.15 lb.
Height	1.83 in
Width	1.49 in
Dimensions	4.18 in x 1.49 in x 1.83 in

General

Color	Brown
Style	Single Pole
Series	General Purpose
Specifications	• Auto Grounding Mounting Bridge - Zinc Plated Steel • Base Material - Thermoplastic, Black • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Terminal Screws - Brass • Toggle Material - Nylon • Top Material - Thermoplastic, Gray
UPC	783585153759
Type	Toggle
Item Type	Single Pole Commercial Toggle Switch
Material	Nylon

Logistics

Pallet Quantity	5000
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)

