

Straight Blade Devices, Receptacles,
Duplex, Decorator, Commercial/Industrial
Grade, 2-Pole 3-Wire Grounding, 20A 125V,
5-20R, White, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [DR20WHI](#)

Straight Blade Devices, Receptacles, Duplex, Decorator,
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 20A
125V, 5-20R, White, Single Pack

Features

- Aesthetic Style Line® decorator design
- Smooth face
- Triple wipe contacts

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-2, Environmental - Operating Temperatures - Maximum
continuous 75°C minimum -40°C (w/o impact), Mechanical -
Product Identification - Ratings are a permanent part of the
device, Mechanical - Terminal Accommodation - #12-#10 AWG
copper stranded or solid conductor only, Mechanical - Terminal
Identification - Terminals identified in accordance with UL 498
and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Connectivity	Back and Side Wired
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.29 in
Width	1.06 in
Dimensions	3.28 in x 1.06 in x 1.29 in

General

Color	White
Style	Style Line Decorator
Series	Commercial Specification Grade

Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Galvanized Steel • Mounting Strap - .040 in. (1) Galvanized steel • Power Contacts - .030 in. (.8) Brass • Terminal Screws - Plated steel • Wire Clamp - .062 in. (1.6) Nickel plated steel
UPC	783585127903
Type	Standard Duplex
Material - Mounting Hardware	Screw Mounting
Item Type	Decorator Duplex
Material	Nylon

Logistics

Pallet Quantity	8500
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without impact
-----------------------	---

Horsepower - Maximum1

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [French, English]



A Hubbell brand