

Switches and Lighting Control, Decorator
Switch, Specification Grade, Three Way,
15A 120/277V AC, Back and Side Wired,
White

By Hubbell Wiring Device-Kellems
Catalog # [DS315W](#)

Switches and Lighting Control, Decorator Switch, Specification
Grade, Three Way, 15A 120/277V AC, Back and Side Wired, White

Features

- Thread cleaning captive mounting screw
- Steel, zinc plated bridge is corrosion resistant
- Automatic self-grounding staple

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum
for 1 minute, Electrical - Max. Continuous Current - 15A, Electrical
- Max. Working Voltage - 277V AC, Electrical - Overload -
Minimum 4.8 times rated current for 100 cycles, Electrical -
Temperature Rise - 30°C maximum at rated current,
Environmental - Flammability - UL 94V-2, Environmental -
Operating Temperature - Max. continuous: 75°C, Min. continuous:
-40°C without impact, Mechanical - Terminal Accommodations -
#14 AWG min. - #10 AWG max. solid and stranded copper wire
only

Specifications

EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Single Pole

Current

Amperage Rating	15 A
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A

Dimensions

Length	3.91 in
--------	---------



Weight	0.2 lb.
Height	1.01 in
Width	1.41 in
Dimensions	3.91 in x 1.41 in x 1.01 in

General

Color	White
Style	Three Way
Series	General Purpose
Specifications	• Contacts - Silver Alloy • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Mounting Bridge - Nickel Plated Steel with Auto Ground Staple • Rocker Material - Thermoplastic • Terminal Screws - Brass
UPC	783585108346
Type	Rocker/Decorator
Item Type	Three Way Style Line Decorator Switch
Material	Thermoplastic

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Action	SPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)