

Power Protection Devices, Receptacle, Self
Test, GFCI, TR, Commercial Grade, 20A 125V,
2-Pole 3-Wire Grounding, 5- 20R, Black

By Hubbell Wiring Device-Kellems
Catalog # [GFRTR20BLK](#)

Power Protection Devices, Receptacle, Self Test, GFCI, TR, Commercial
Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5- 20R, Black

Features

- Patented shutter design for tamper-resistant
- Compliant with NEC® 406.12 and NEC® 517-18(c)
- Patented AUTOGUARD® self test technology
- Triple wipe construction

Specifications

Nema Rating	5-20R
Industry Standard(s)	Meets All NEC® Requirements

Current

Voltage Rating Description	125 V
Current / Amperage Rating	20 A

Dimensions

Weight	0.35 lb.
--------	----------

General

Specifications	• Base - Nylon
----------------	--



- Face - Nylon
 - Ground Contacts - Brass
 - Mounting Screws - Zinc plated steel
 - Mounting Strap - Zinc plated steel
 - Power Contacts - Brass
- Black
Standard
883778999635
Tamper-Resistant
Heavy Duty

Color
Style
UPC
Type
Series

Logistics

Pallet Quantity	2240
Carton Quantity	10

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)