

Power Protection Devices, Receptacle, Self
Test, GFCI, TRWR, Commercial Grade, 15A
125V, 2-Pole 3-Wire Grounding, 5-15R, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [GFRTW15I](#)

Power Protection Devices, Receptacle, Self Test, GFCI, TRWR,
Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Ivory

Features

- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for TR (517-18c) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired
- Single LED status indicator - green indicates power, red indicates a trip, flashing red indicates end of life

Specifications

Nema Rating	5-15R
Industry Standard(s)	Meets All NEC® Requirements

Current

Voltage Rating Description	125 V
Current / Amperage Rating	15 A

Dimensions

Weight	0.35 lb.
--------	----------

General

Specifications

Color
Style
UPC
Type

Series

Logistics

Pallet Quantity	2240
Carton Quantity	10

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)



- Base - Nylon
 - Face - Nylon
 - Ground Contacts - Brass
 - Mounting Screws - Zinc plated steel
 - Mounting Strap - Zinc plated steel
 - Power Contacts - Brass
- Ivory
Standard
883778999314
Tamper-Resistant, Weather
Resistant
Heavy Duty