

Power Protection Devices, Receptacle, Self
Test, GFCI, WR, Commercial Grade, 20A
125V, 2-Pole 3-Wire Grounding, 5-20R, White

By Hubbell Wiring Device-Kellems
Catalog # [GFRWR20W](#)

Power Protection Devices, Receptacle, Self Test, GFCI, WR, Commercial
Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, White

Features

- Patented AUTOGUARD® self test technology
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Single LED status indicator - green indicates power, red indicates a trip, flashing red indicates end of life

Specifications

Nema Rating	5-20R
Industry Standard(s)	Meets All NEC® Requirements

Current

Voltage Rating Description	125 V
Current / Amperage Rating	20 A

Dimensions

Weight	0.35 lb.
--------	----------

General

Specifications	• Base - Nylon
----------------	--



- Face - Nylon
- Ground Contacts - Brass
- Mounting Screws - Zinc plated steel
- Mounting Strap - Zinc plated steel
- Power Contacts - Brass

Color	White
Style	Standard
UPC	883778999833
Type	Weather Resistant
Series	Heavy Duty

Logistics

Pallet Quantity	2240
Carton Quantity	10

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)