



Motorized Cord Reels

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight lbs (kg)	Catalog Number
White motorized reel without end effectors.	20	125V	75 (22.9)	12/3 SJO	40 (18.1)	HBLM75123
White motorized reel without end effectors.	20	125/250	75 (22.9)	12/4 SJO	43 (19.5)	HBLM75124
White motorized reel with (1) L14 20A Twist Lock® plug and (1) female L14 plug.	20	125/250	75 (22.9)	12/4 SJO	37 (16.8)	HBLM75124C
White motorized reel with (1) L14 20A Twist Lock® plug and (2) 20A duplex receptacles.	30	125/250	25 (7.6)	10/4 SJO	36 (16.3)	HBLM25104SC
White motorized reel without end effectors.	30	125	45 (13.7)	10/3 SJO	40 (18.1)	HBLM45103
White motorized reel without end effectors.	30	125/250	45 (13.7)	10/4 SJO	45 (20.4)	HBLM45104
White motorized reel with (1) L14 20A Twist Lock® plug and (1) female L14 plug.	30	125/250	45 (13.7)	10/4 SJO	36 (16.3)	HBLM45104C
White motorized reel with (1) L14 20A Twist Lock® plug and (2) 20A duplex receptacles.	30	125/250	45 (13.7)	10/4 SJO	36 (16.3)	HBLM45104SC
White motorized reel without end effectors.	30	125	60 (18.3)	10/3 SJO	44 (22.0)	HBLM60103

*Note: Configured reels are supplied with HBL5366CST on the power supply cord. | *Options also available in 45 feet. Modify the length indication in the catalog number (ex. HBLM45123C20) | **For white cord, modify part number to HBLMWCxxxx. Ex. HBLMWC25123. For black housing, add suffix "BLK". Ex. HBLM45123BLK.*

Motorized Cord Reels

Description	Catalog Number
Low voltage, decorator push-button switch, single pole, momentary contact, 100mA 30V DC, two button, white.	DSM30W2
Low voltage, specification grade, toggle switch, momentary, single pole double throw, 5A 24V DC, white.	HBL1557WLV
Industrial grade, toggle switch, momentary single pole, double throw center off, 15A 120/277V AC.	HBL1556LW
Locking key for HBL1556LW.	HBL1209
Industrial grade, toggle switch, momentary single pole, double throw center off, 15A 120/277V AC.	HBL1556W
Mounting bracket.	HBLIMB
Mounting bracket with junction box mount.	HBLIMBJ
Plenum rated enclosure.	HBLIPRBOX



HBLM25123



HBLM25123BLK



HBLMWC25123



HBLM25123C20



HBL25123R220M1

Dimensions in Inches (mm)