

Extra Heavy Duty Industrial Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 20A, Gray

By Hubbell Wiring Device-Kellems
Catalog # [GFSG5362GRY](#)



Industrial Grade TRWR Ground Fault Receptacle 20A

Features

- Heavy duty robust construction, high impact resistant polyester housing
- Corrosion Resistant: nickel-plated face contacts, mounting strap, line/load terminals and terminal clamps, stainless steel screws
- Patented auto monitor, power denial technology

Application

Industrial Grade

Specifications

Industry Standard(s)	UL 943 and Meets All NEC® Requirements
Nema Rating	5-20R

Conductor

Wire Size	#14 - #10 AWG
-----------	---------------

Current

Phase	Single Phase
Current / Amperage Rating	20 A
Wattage	2500 W
Voltage Rating	125 VAC

Dimensions

Size	4.06 in x 1.75 in x 1.48 in
Width	1.75 in

Height	4.06 in
Length	1.48 in
Dimensions	1.48 in x 1.75 in x 4.06 in

General

Item Type	Style Line GFCI Receptacle Tamper-Resistant/Weather-Resistant
Type	Extra Heavy Duty
Material	PC/PBT
Specifications	<ul style="list-style-type: none">• Base - Nylon• Face - PC/PBT• Ground Contacts - Nickel Plated Brass• Mounting Screws - Stainless Steel• Mounting Strap -Nickel Plated Brass
UPC	783585745954
Color	Gray

Logistics

Carton Quantity	10
Pallet Quantity	1440

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)