

Extra Heavy Duty Industrial Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 20A, Red

By Hubbell Wiring Device-Kellems
Catalog # [GFSG5362R](#)

Industrial Grade TRWR Ground Fault Receptacle 20A

Features

- Heavy duty robust construction, high impact resistant polyester housing
- Corrosion Resistant: nickel-plated face contacts, mounting strap, line/load terminals and terminal clamps, stainless steel screws
- Patented auto monitor, power denial technology

Application

Industrial Grade

Specifications

Nema Rating	5-20R
Industry Standard(s)	UL 943 and Meets All NEC® Requirements

Conductor

Wire Size	#14 - #10 AWG
-----------	---------------

Current

Voltage Rating	125 VAC
Wattage	2500 W
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Weight	0.45 lb.
Height	4.06 in



Width	1.75 in
Length	1.48 in
Size	4.06 in x 1.75 in x 1.48 in
Dimensions	1.48 in x 1.75 in x 4.06 in

General

Specifications	• Base - Nylon • Face - PC/PBT • Ground Contacts - Nickel Plated Brass • Mounting Screws - Stainless Steel • Mounting Strap -Nickel Plated Brass
Color	Red
UPC	783585745978
Type	Tamper-Resistant/Weather-Resistant
Item Type	Style Line GFCI Receptacle
Material	PC/PBT
Series	Extra Heavy Duty

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)