

Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 3/4", Steel, Insulated

By Hubbell Wiring Device-Kellems
Catalog # [H0751](#)

Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 3/4", Steel, Insulated

Features

- Hexagonal nut compresses gland-ring onto conduit
- Nylon gasket provides liquidtight seal at hub
- Non-integral steel ferrule seals conduit

Application

For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• CSA Certified • UL 514B

Dimensions

Trade Size	3/4
Dimension - Width mm	1.453 in
Dimension - Thread Size	3/4"-14 NPT

General



Style	Straight
Specifications	• Compression Nut - Zinc plated steel • Ferrule - Zinc plated steel • Fitting - Zinc plated steel • Insulator - Nylon • Locknut - Zinc plated steel • Split Seal Ring - Nylon • Washer - Nylon
UPC	783585035130
Type	Metallic Liquidtight Fittings
Material	Steel, Zinc Plated

Logistics

Pallet Quantity	9000
Carton Quantity	25

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)