

Kellems Wire Management, Liquidtight
System, Straight Male Type A Connector,
3/4", Steel

By Hubbell Wiring Device-Kellems
Catalog # [H075CNK](#)

Kellems Wire Management, Liquidtight System, Straight Male
Type A Connector, 3/4", Steel

Features

- Helps prevent conduit pull-out and damage at fitting
- Reduces equipment downtime

Performance

Environmental - Flammability - UL 94-HB and UL 94-V2,
Environmental - Hazardous Location - Suitable for use in
hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III,
Div. 1 & 2, Environmental - Operating Temperature - -30°F to
+225°F (-34°C to +107°C)

Specifications

Industry Standard(s)	UL Listed
EU RoHS Indicator	Contact Manufacturer

Dimensions

Conduit Trade Size	3/4 in
--------------------	--------

General

Specifications

Style
UPC
Type
Material
Series

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)



- Conduit Trade Size - 3/4
Inch
 - NPT Fitting Size - 3/4 Inch
 - Strand - Stainless Steel
 - Strand Length - 6.25" (15.87)
- For UL Type A
783585334806
Straight With Male Fitting
Steel Fitting, Stainless Steel
Mesh
Liquidtight Conduit