

Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1", Steel, Insulated

By Hubbell Wiring Device-Kellems
Catalog # [H1001](#)

Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1", Steel, Insulated

Features

- Hexagonal nut compresses gland-ring onto conduit
- Nylon gasket provides liquidtight seal at hub
- Non-integral steel ferrule seals conduit

Application

For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• CSA Certified • UL 514B

Dimensions

Trade Size	1
Dimension - Width mm	1.719 in
Dimension - Thread Size	1"-11-1/2 NPT

General



Style	Straight
Specifications	• Compression Nut - Zinc plated steel • Ferrule - Zinc plated steel • Fitting - Zinc plated steel • Insulator - Nylon • Locknut - Zinc plated steel • Split Seal Ring - Nylon • Washer - Nylon
UPC	783585035147
Type	Metallic Liquidtight Fittings
Material	Steel, Zinc Plated

Logistics

Pallet Quantity	6300
Carton Quantity	10

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)