

Kellems Wire Management, Liquidtight
System, Straight Male Type A Connector, 1
1/2", Steel

By Hubbell Wiring Device-Kellems
Catalog # [H150CNK](#)

Kellems Wire Management, Liquidtight System, Straight Male
Type A Connector, 1 1/2", Steel

Features

- Helps prevent conduit pull-out and damage at fitting
- Reduces equipment downtime

Performance

Environmental - Flammability - UL 94-HB and UL 94-V2,
Environmental - Hazardous Location - Suitable for use in
hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III,
Div. 1 & 2, Environmental - Operating Temperature - -30°F to
+225°F (-34°C to +107°C)

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	UL Listed

Dimensions

Conduit Trade Size	1 1/2 in
--------------------	----------

General

Style
Series
Specifications

UPC
Type
Material

Logistics

Carton Quantity	2
-----------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)



For UL Type A
Liquidtight Conduit

- Conduit Trade Size - 1 1/2
Inch
- NPT Fitting Size - 1 1/2 Inch
- Strand - Stainless Steel
- Strand Length - 13.5" (34.29)

783585334837
Straight With Male Fitting
Steel Fitting, Stainless Steel
Mesh