

Straight Blade Devices, IEC 320 Devices,
Inlet, 16A 250V, International Rated,
Pressure Screw Terminal, Black, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [H320B](#)

Straight Blade Devices, IEC 320 Devices, Inlet, 16A 250V,
International Rated, Pressure Screw Terminal, Black, Single Pack

Features

- Compatible with IEC320
- Low profile
- Impact resistant

Application

Heavy Duty Industrial

Performance

Electrical - Dielectric Voltage - Withstands 2,000V minimum,
Electrical - Rating - 16A 250V AC for European service, 20A
250V AC for North American service, Environmental -
Flammability - UL 94V-2, Environmental - Operating
Temperatures - Maximum continuous 75°C minimum -40°C (w/o
impact), Mechanical - Terminal Accommodation - North
American - #16-12 AWG stranded or solid copper conductor only.

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA
Industry Standard(s)	• CSA certified 20A 250V AC-File No. 17337 • TUV and VDE Certified • UL classified to IEC 320, 16A 250V AC-File No. E111246 • UL Listed 20A 250V AC-File No. E1706

Conductor

Number Of Wires	3-Wire
Wire Size	• North American-#16AWG-#12AWG • International-1.55mm²-2.5mm².
Number Of Poles	2-Pole

Current

Amperage Rating	20/16 A
Voltage Rating Description	250 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	20/16 A
Voltage Rating	250 V
Wattage	7500 W
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20/16 A

Dimensions

Length	1.47 in
Display Size	Standard Sized Product
Weight	0.05 lb.
Height	1.19 in
Width	1.64 in
Dimensions	1.47 in x 1.64 in x 1.19 in

General

Color	Black
Specifications	• Assembly Screws - Zinc plated steel • Configuration - IEC 60320-1 Style appliance coupler, C20 • Contact Blades - .040" (1.0) Brass • Device Type - 2 Pole + earth • Terminal Clamp - Nickel plated steel • Terminal Retainer - Nylon • Terminal Screws - Stainless steel
UPC	783585777092
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	Chassis Single
Material	Nylon

Logistics

Pallet Quantity	6000
Carton Quantity	10

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
--------------------	--

Operating Temperature

Maximum continuous 75°C and
minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand