

Straight Blade Devices, IEC 320 Devices,
Female Connector, 16A 250V, International
Rated, Pressure Screw Terminal, Black,
Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [H320C](#)

Straight Blade Devices, IEC 320 Devices, Female Connector, 16A 250V, International Rated, Pressure Screw Terminal, Black, Single Pack

Features

- Compatible with IEC320
- Hinged one piece body design for easy assembly
- Two captive multiple drive assembly screws

Performance

Electrical - Dielectric Voltage - Withstands 2,000V minimum, Electrical - Rating - 16A 250V AC for European service, 20A 250V AC for North American service, Environmental - Flammability - UL 94 HB or better, Environmental - IP Suitability - IP20, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Cord Accommodation - .325" - .475" (8.0-12.0), Mechanical - Terminal Accommodation - North American - #16-12 AWG stranded or solid copper conductor only,International - 1.55mm²-2.5mm²,Terminal Identification Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA
Industry Standard(s)	• CSA certified 20A 250V AC-File No. 17337 • UL classified to IEC 320, 16A 250V AC-File No. E111246 • UL Listed 20A 250V AC-File No. E1706

Conductor

Number Of Conductors	3-Wire Grounding
Number Of Wires	3-Wire
Wire Size	• North American-#16AWG-#12AWG • International-1.55mm²-2.5mm².
Number Of Poles	2-Pole
Conductor Range	#14 AWG to #12 AWG



Current

Amperage Rating	20/16 A
Voltage Rating Description	250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20/16 A
Voltage Rating	250 V
Wattage	7500 W
Connectivity	Screw Terminals
Current / Amperage Rating	20/16 A

Dimensions

Length	2.74 in
Display Size	Standard Sized Product
Weight	0.2 lb.
Height	1.36 in
Width	1.42 in
Dimensions	2.74 in x 1.42 in x 1.36 in

General

Color	Black
Cord Range	• 0.325"-0 • .475" • (8.0-12.0)
Specifications	• • Terminal Retainer - Nylon • Assembly Screws - Zinc plated steel • Configuration - IEC 60320-1 Style appliance coupler, C19 • Device Type - 2 Pole + earth • Power Contacts - • .032" (.81) Brass • Terminal Clamp - Nickel plated steel • Terminal Screws - Stainless steel
UPC	783585777108
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	Valise
Material	Nylon

Logistics

Pallet Quantity	6000
Carton Quantity	10

Operational

Temperature Rating	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
--------------------	--

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand