

Straight Blade Devices, IEC 320 Devices,
Female Receptacle, 16A 250V, International
Rated, Pressure Screw Terminal, Black,
Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [H320R](#)

Straight Blade Devices, IEC 320 Devices, Female Receptacle, 16A 250V, International Rated, Pressure Screw Terminal, Black, Single Pack

Features

- Compatible with IEC320
- Low profile
- Impact resistant

Application

Heavy Duty

Performance

Electrical:Dielectric Voltage Withstands 2,000V minimum,Rating 16A 250V AC for European service, 20A 250V AC for ,North American service, Mechanical:Terminal Accommodation North American – #16-12 AWG stranded or solid copper conductor only. International – 1.55mm²-2.5mm² ,Terminal Identification: Terminals identified in accordance with UL 498 and CSA, Environmental:Flammability UL 94 VO ,Operating Temperatures Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA
Industry Standard(s)	• CSA certified 20A 250V AC-File No. 17337 • UL Listed 20A 250V AC-File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	• North American-#16AWG-#12AWG • International-1.55mm²-2.5mm².
Number Of Poles	2-Pole

Current

Amperage Rating	20/16 A
Voltage Rating Description	250 V



Dielectric Strength	Withstands 2,000V minimum
Current Rating	20/16 A
Voltage Rating	250 V
Wattage	7500 W
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20/16 A

Dimensions

Length	1.41 in
Display Size	Standard Sized Product
Weight	0.1 lb.
Height	1.52 in
Width	1.89 in
Dimensions	1.41 in x 1.89 in x 1.52 in

General

Color	Black
Specifications	• Assembly Screws - Zinc plated steel • Device Type - 2 Pole + earth • Housing - Nylon • Power Contacts - .032" (.81) Brass • Terminal Clamp - Nickel plated steel • Terminal Retainer - Nylon • Terminal Screws - Stainless steel
UPC	783585777054
Material - Mounting Hardware	Screw Mounting
Item Type	IEC Appliance Coupler Single

Logistics

Pallet Quantity	2640
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- Catalog [English]
 - Catalog Page [English]
 - Catalog Page [English]
 - Installation Manual [French]
-

