







10A 250V AC 20A 125V AC Horsepower Rated 3/4 HP, 125-250V AC

Description		Terminal	Catalog Number
Single pole/ single throw.		Screw Spade	HBL11 HBL11SP
Single pole/ single throw momentary.		Screw Spade	HBL11M HBL11SPM
Single pole/ double throw.		Screw Spade	HBL12 HBL12SP
Single pole/ double throw 3-position center OFF.		Screw Spade	HBL123 HBL123SP
Single pole/ double throw 3-position center OFF momentary.		Screw Spade	HBL123MM HBL123SPMM

Note: All threaded stems 15/32 in.-32 thread.




10A 240V AC 15A 120V AC

Description		Terminal	Catalog Number
Single pole/ single throw.		Screw	HBL118

Note: 15/32 in.-32 thread.

4A 250V 8A 125V 10A 120V AC 1/3 HP 120V AC

Description		Terminal	Catalog Number
Single pole/ single throw.		#18 Std. AWG Copper Wire Leads 105° C Black.	HBL11WL

Note: 15/32 in.-32 thread, keyway .080 x .035.

Specifications

Impact Resistant Thermoplastic Body.
Fine Silver Contacts.
Knurled Nut, Hex Nut And Strap All Nickel Plated.
Keyed Brass Bushing Nickel Plated.
Brass Toggle Nickel Plated.
Choice of Terminal Design: .250 in. (6.3) Male Tab Spade Type or 6/32 Screw Type.
UL Recognized.

Dimensions in Inches (mm)