

Commercial Grade, Panel Mount and
Specialty Switches, Bat Handle Switches,
Momentary Single Pole Single Throw 10A
250V/10A 125V, Terminal

By Hubbell Wiring Device-Kellems
Catalog # [HBL11M](#)

Switches and Lighting Controls, Commercial Grade, Panel Mount
and Specialty Switches, Bat Handle Switches, Momentary Single
Pole Single Throw 10A 250V/10A 125V, Terminal

Features

- Nickel Plated for Corrosion Resistance

Performance

Environmental - Operating Temperatures - Max Continuous- 75
°C, Minimum -40 °C Without Impact

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Number Of Poles	Single Pole
-----------------	-------------

Configuration

Mounting Method	Panel Mount
Contact Configuration	Momentary

Current

Amperage Rating	10/20 A
Voltage Rating	250/125 VAC
Connectivity	Screw Terminals
Current / Amperage Rating	10/20 A

Dimensions

Length	2.15 in
Weight	0.05 lb.
Height	1.12 in
Width	0.56 in
Dimensions	2.15 in x 0.56 in x 1.12 in



General

Color	Metallic
Style	Screw Terminal
Series	Single Pole/Single Throw
Specifications	- Body Material - Impact Resistant Thermoplastic Body - Bushing - Brass- Nickel Plated - Contacts - Fine Silver - Strap Material - Nickel Plated - Toggle - Brass- Nickel Plated
UPC	783585016689
Type	Momentary
Item Type	Panel Mount and Bat Handle Switch

Logistics

Carton Quantity	10
-----------------	----

Operational

Action	SPST
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.75

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)