

Commercial Grade, Panel Mount and
Specialty Switches, Bat Handle Switches,
Momentary Single Pole Double Throw
Center Off, 10A 250V/10A

By Hubbell Wiring Device-Kellems
Catalog # [HBL123SPMM](#)

Switches and Lighting Controls, Commercial Grade, Panel Mount
and Specialty Switches, Bat Handle Switches, Momentary Single
Pole Double Throw Center Off, 10A 250V/10A

Features

- Nickel Plated for Corrosion Resistance

Performance

Environmental - Operating Temperatures - Max Continuous- 75
°C, Minimum -40 °C Without Impact

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Number Of Poles	Single Pole
-----------------	-------------

Configuration

Mounting Method	Panel Mount
Contact Configuration	Momentary

Current

Amperage Rating	10/20 A
Voltage Rating	250/125 VAC
Current / Amperage Rating	10/20 A

Dimensions

Length	2.15 in
Weight	0.1 lb.
Height	1.12 in
Width	0.56 in
Dimensions	2.15 in x 0.56 in x 1.12 in



General

Style	Spade Terminal
Series	Single Pole/Double Throw
Specifications	- Body Material - Impact Resistant Thermoplastic Body - Bushing - Brass- Nickel Plated - Contacts - Fine Silver - Strap Material - Nickel Plated - Toggle - Brass- Nickel Plated
UPC	783585016795
Type	Momentary
Item Type	Panel Mount and Bat Handle Switch

Logistics

Carton Quantity	100
-----------------	-----

Operational

Action	SPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.75

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)