

Industrial Grade Double Pole Double Throw
Toggle Switch, AC, 15A 120/277V, Brown

By Hubbell Wiring Device-Kellems
Catalog # [HBL1382](#)

Switches and Lighting Controls, Extra Heavy Duty Industrial Grade, Toggle Switches, General Purpose AC, Double Pole Double Throw Center Off, 15A 120/277V AC, Back and Side Wired, Brown Toggle

Features

- Features large brass binding head screws with deep slots for easy installation
- Equipped with an abuse-resistant nylon toggle for enhanced durability
- Includes a strip gauge to ensure precise wiring

Application

Back and Side Wired

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum for 1 minute, Electrical - Max. Continuous Current - 20A, Electrical - Max. Working Voltage - 277V AC, Electrical - Overload - Minimum 4.8 times rated current for 100 cycles, Electrical - Temperature Rise - 30°C maximum at rated current, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact, Mechanical - Terminal Accommodations - #14 AWG min. - #10 AWG max. Solid and stranded copper wire only

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Double Pole

Current

Amperage Rating	15 A
Voltage Rating Description	120-277 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current



Connectivity	Back and Side Wired
Current / Amperage Rating	15 A

Dimensions

Length	4.06 in
Weight	0.25 lb.
Height	1.89 in
Width	1.31 in
Dimensions	4.06 in x 1.31 in x 1.89 in

General

Color	Brown
Style	Double Pole Double Throw
Series	Extra Heavy Duty
Specifications	• Base Material - Thermoset, Blue • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Terminal Screws - Brass • Toggle Material - Nylon • Top Material - Thermoset
UPC	783585432540
Type	Toggle

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Action	DPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish\]](#)