

Industrial Grade, Locking Switches, General Purpose AC, Maintained Double Pole Double Throw Center Off, 20A 120/277V AC Black Key Guide

By Hubbell Wiring Device-Kellems
Catalog # [HBL1386L](#)

Switches and Lighting Controls, Industrial Grade, Locking Switches, General Purpose AC, Maintained Double Pole Double Throw Center Off , 20A 120/277V AC, Terminal Screws Black Key Guide

Features

- Large brass binding head screws with deep slots
- Lock circuits On or Off
- Strip gauge for accurate wiring

Application

Back and Side Wired

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum for 1 minute, Electrical - Max. Continuous Current - 20A, Electrical - Max. Working Voltage - 277V AC, Electrical - Overload - Minimum 4.8 times rated current for 100 cycles, Electrical - Temperature Rise - 30°C maximum at rated current, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact, Mechanical - Terminal Accommodations - #14 AWG min. - #10 AWG max. Solid and stranded copper wire only

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Double Pole

Current

Amperage Rating	20 A
Voltage Rating Description	120-277 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	20 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current
Connectivity	Back and Side Wired



Current / Amperage Rating	20 A
---------------------------	------

Dimensions

Length	4.06 in
Weight	0.25 lb.
Height	1.19 in
Width	1.31 in
Dimensions	4.06 in x 1.31 in x 1.19 in

General

Color	Black
Style	Double Pole Double Throw
Series	Extra Heavy Duty
Specifications	• Base Material - Thermoset, Green • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Key Guide - Metallic, Black • Terminal Screws - Brass • Top Material - Thermoset
UPC	783585432687
Type	Toggle

Logistics

Carton Quantity	10
-----------------	----

Operational

Action	DPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish\]](#)