

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Non-Metallic NEMA 1 Enclosure, For 30A Devices, Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL1390](#)

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Non-Metallic NEMA 1 Enclosure, For 30A Devices , Black

Features

- All Aluminum Cover and Base
- Top, bottom or back wire entry points
- Base is pre-drilled for rear surface mounting

Application

For 30A Switches

Performance

Environmental - Operating Temperatures - Max Continuous- 75 °C, Minimum- -40 °C w/o Impact

Specifications

Environmental Conditions	Indoor Only
EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Current

Amperage Rating	30 A
Current Rating	30 A

Dimensions

Length	4.52 in
Weight	1.05 lb.
Height	3.43 in



Width	3.97 in
Dimensions	4.52 in x 3.97 in x 3.43 in

General

Style	Standard Duty
Enclosure Type	NEMA 1
Series	Non-Fused
Specifications	• Base Material - Aluminum • Cover Material - Aluminum • No. Equipment Grounds - 2
UPC	783585017020
Type	Enclosures without Switch

Logistics

Pallet Quantity	810
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	20

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)