

HUBBELL
Wiring Device-Kellems

**Locking Devices, Hubbellock, Industrial,
Flush Receptacle, 30A 3-Phase Delta 480V
AC, 3-Pole 4-Wire Grounding, Non-NEMA,
Screw Terminal, Red**

By Hubbell Wiring Device-Kellems
Catalog # [HBL20443](#)

Locking Devices, Hubbellock, Industrial, Flush Receptacle, 30A 3-
Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Non-NEMA,
Screw Terminal, Red



Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Thermoset molded housing provides maximum heat resistance

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0 for Receptacles and Inlets.HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #10 AWG - #6 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No

Conductor

Number Of Wires	4-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	480 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A

Voltage Rating	480 VAC
Connectivity	Screw Terminals
Current / Amperage Rating	30 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.55 lb.
Height	1.75 in
Width	1.94 in
Dimensions	3.28 in x 1.94 in x 1.75 in

General

Color	Red
Specifications	• Bridge - Zinc plated steel • Contacts - Bronze • Device Color - Black/Red Shutter • Housing - Thermoset • Shutter - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017419
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	30A Grounding Hubbellock® Receptacle
Material	Thermoplastic

Logistics

Pallet Quantity	3060
Carton Quantity	20

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French\]](#)

