

Hubbell-PRO Extra Heavy Duty, Straight Blade Specification Grade Duplex Receptacles



Specifications

Receptacle, Smooth Nylon Face	Part	Description
Typical Specification – Catalog No. 5252AB Manufacturer's Identification – Hubbell 5252AB Receptacle Description – Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Certification – UL Listed to UL498 File E2186 Fed. Spec. W596, Certified to CSA 22.2, No. 42 NEMA® WD-6 Compliant	Receptacle Top Base Triple Wipe Power Contacts Wire Clamp Mounting Strap Ground Contact Line Terminal Screws Ground Screw Center Assembly Staple Automatic Self-Grounding Staple Mounting Screws	15A Polycarbonate Polycarbonate .031 in. (.8) Brass .062 in. (1.8) Steel-Nickel Finish .040 in. (1) Galvanized Steel .031 in. (.8) Brass #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive .040 in. (1) Galvanized Steel Stainless Steel Zinc Plated Steel
Receptacle, Finder Groove Face	Part	Description
Typical Specification – Catalog No. 5262B Manufacturer's Identification – Hubbell 5262B Receptacle Description – Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Certification – UL Listed to UL498 File E2186 Fed. Spec. W596, Certified to CSA C22.2, No. 42 NEMA® WD-6 Compliant	Receptacle Top Base Triple Wipe Power Contacts Wire Clamp Mounting Strap Ground Contact Line Terminal Screws Ground Screw Center Assembly Staple Automatic Self-Grounding Clip Mounting Screws	15A Polycarbonate RTP* .031 in. (.8) Brass .062 in. (1.8) Steel-Nickel Finish .050 in. (1) Galvanized Steel .031 in. (.8) Brass #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive .040 in. (1) Galvanized Steel Stainless Steel Zinc Plated Steel

Performance

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL 498 and CSA (Brass, White, Green).
Terminal Accommodation	#14-10 AWG stranded or solid copper conductor only.
Product Identification	Ratings are a permanent part of the device.
Environmental – Material	
Flammability	UL 94V-2.
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact).

Note: Please consult the factory for product dimensions and specifications of other products listed in this catalog.

NEMA is a registered trademark of the National Electrical Manufacturers Association.

Dimensions in Inches (mm)