

HUBBELL
Wiring Device-Kellems

**Locking Devices, Hubbellock, Industrial,
Flanged Receptacle, 30A 600V AC, 20A
250V DC, 3-Pole 4-Wire Grounding, Non-
NEMA**

By Hubbell Wiring Device-Kellems
Catalog # [HBL21420](#)

Locking Devices, Hubbellock, Industrial, Flanged Receptacle, 30A
600V AC, 20A 250V DC, 3-Pole 4-Wire Grounding, Non- NEMA,
Screw Terminal, Cast Aluminum, Angled Surface Mounted
Housing.



Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Angled housing reduces the profile of the device and makes mating and un-mating easier
- Metallic weather protective spring loaded cover provides protection from moisture and dust

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0 for Receptacles and Inlets.HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #10 AWG - #6 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No

Conductor

Number Of Wires	4-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	250 VDC/600 VAC



Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VDC/600 VAC
Connectivity	Back Wired Screw Terminals
Current / Amperage Rating	30 A

Dimensions

Length	5.93 in
Display Size	Standard Sized Product
Weight	2 lb.
Height	5.09 in
Width	3.06 in
Dimensions	5.93 in x 3.06 in x 5.09 in

General

Color	Metallic
Specifications	• Contacts - Bronze • Housing - Cast Aluminum • Receptacle Interior - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017426
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	20A/30A Grounding Hubbellock® Receptacle
Material	Aluminum, Cast

Logistics

Pallet Quantity	360
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)