

Commercial Grade, Panel Mount and
Specialty Switches, Bat Handle Switches,
Double Pole Double Throw Center Off 10A
250V/10A 125V, Screw

By Hubbell Wiring Device-Kellems
Catalog # [HBL223](#)

Switches and Lighting Controls, Commercial Grade, Panel Mount
and Specialty Switches, Bat Handle Switches, Double Pole
Double Throw Center Off 10A 250V/10A 125V, Screw

Features

- Nickel Plated for Corrosion Resistance

Performance

Environmental - Operating Temperatures - Max Continuous- 75 °C, Minimum -40 °C Without Impact

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Number Of Poles	Double Pole
-----------------	-------------

Configuration

Mounting Method	Panel Mount
-----------------	-------------

Current

Amperage Rating	10/20 A
Voltage Rating	250/125 VAC
Connectivity	Screw Terminals
Current / Amperage Rating	10/20 A

Dimensions

Length	2.27 in
Weight	0.1 lb.
Height	1.3 in
Width	0.76 in
Dimensions	2.27 in x 0.76 in x 1.3 in



General

Color	Metallic
Style	Screw Terminal
Series	Double Pole/Double Throw
Specifications	- Body Material - Impact Resistant Thermoplastic Body - Bushing - Brass- Nickel Plated - Contacts - Fine Silver - Strap Material - Nickel Plated - Toggle - Brass- Nickel Plated
UPC	783585017136
Type	General Purpose
Item Type	Panel Mount and Bat Handle Switch

Logistics

Carton Quantity	10
-----------------	----

Operational

Action	DPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.5

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)