

Commercial Grade, Panel Mount and  
Specialty Switches, Bat Handle Switches,  
Momentary Double Pole DoubleThrow  
Center Off 10A 250V/10A

By Hubbell Wiring Device-Kellems  
Catalog # [HBL223MM](#)

Switches and Lighting Controls, Commercial Grade, Panel Mount  
and Specialty Switches, Bat Handle Switches, Momentary Double  
Pole DoubleThrow Center Off 10A 250V/10A

Features

- Nickel Plated for Corrosion Resistance

Performance

Environmental - Operating Temperatures - Max Continuous- 75  
°C, Minimum -40 °C Without Impact

Specifications

|                      |           |
|----------------------|-----------|
| EU RoHS Indicator    | No        |
| Industry Standard(s) | UL Listed |

Conductor

|                 |             |
|-----------------|-------------|
| Number Of Poles | Double Pole |
|-----------------|-------------|

Configuration

|                       |             |
|-----------------------|-------------|
| Mounting Method       | Panel Mount |
| Contact Configuration | Momentary   |

Current

|                           |                 |
|---------------------------|-----------------|
| Amperage Rating           | 10/20 A         |
| Voltage Rating            | 250/125 VAC     |
| Connectivity              | Screw Terminals |
| Current / Amperage Rating | 10/20 A         |

Dimensions

|            |                            |
|------------|----------------------------|
| Length     | 2.27 in                    |
| Weight     | 0.1 lb.                    |
| Height     | 1.3 in                     |
| Width      | 0.76 in                    |
| Dimensions | 2.27 in x 0.76 in x 1.3 in |



General

|                |                                                                                                                                                                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color          | Metallic                                                                                                                                                                                                                                                         |
| Style          | Screw Terminal                                                                                                                                                                                                                                                   |
| Series         | Double Pole/Double Throw                                                                                                                                                                                                                                         |
| Specifications | <ul style="list-style-type: none"><li>• Body Material - Impact Resistant Thermoplastic Body</li><li>• Bushing - Brass- Nickel Plated</li><li>• Contacts - Fine Silver</li><li>• Strap Material - Nickel Plated</li><li>• Toggle - Brass- Nickel Plated</li></ul> |
| UPC            | 783585313177                                                                                                                                                                                                                                                     |
| Type           | Momentary                                                                                                                                                                                                                                                        |
| Item Type      | Panel Mount and Bat Handle Switch                                                                                                                                                                                                                                |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Action                | DPDT                                                     |
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Horsepower - Maximum  | 1.5                                                      |

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)