

Locking Devices, Hubbellock, Industrial,  
Male Plug, 20A 125V, 2-Pole 3-Wire  
Grounding, Non-NEMA, Screw Terminal,  
Black and White

By Hubbell Wiring Device-Kellems  
Catalog # [HBL23035B](#)

Locking Devices, Hubbellock, Industrial, Male Plug, 20A 125V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Black and White

Features

- Molded-in male contacts are resistant to damage and provide a consistently positive connection
- Insulated non-metallic housing enhances safety and abuse resistance
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Three-piece clamp assembly provides maximum strain relief and protects against entry of moisture and dust

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - HB or better, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #12 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

|                      |                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------|
| EU RoHS Indicator    | Contact Manufacturer                                                                                        |
| Industry Standard(s) | <ul style="list-style-type: none"><li>• Certified to CSA Standard</li><li>• Listed to UL Standard</li></ul> |

Conductor

|                 |                  |
|-----------------|------------------|
| Number Of Wires | 3-Wire           |
| Number Of Poles | 2-Pole           |
| Cable Range     | 0.320 - 0.660 in |

Current

|                            |                           |
|----------------------------|---------------------------|
| Amperage Rating            | 20 A                      |
| Voltage Rating Description | 125 V                     |
| Dielectric Strength        | Withstands 2,000V minimum |



|                           |       |
|---------------------------|-------|
| Voltage Rating            | 125 V |
| Current / Amperage Rating | 20 A  |

Dimensions

|            |                             |
|------------|-----------------------------|
| Length     | 1.72 in                     |
| Weight     | 0.25 lb.                    |
| Height     | 3.22 in                     |
| Width      | 2.31 in                     |
| Dimensions | 1.72 in x 2.31 in x 3.22 in |

General

|                |                                                                                                                                                                                                                                                        |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color          | Black, White                                                                                                                                                                                                                                           |
| Specifications | <ul style="list-style-type: none"><li>• Assembly Screws - Stainless Steel</li><li>• Contacts - Brass</li><li>• Cord Clamp Material - Nylon</li><li>• Device Color - Black/White</li><li>• Housing - Nylon</li><li>• Plug Housing - Thermoset</li></ul> |
| UPC            | 783585017440                                                                                                                                                                                                                                           |
| Type           | Plugs                                                                                                                                                                                                                                                  |
| Item Type      | 20A Hubbellock® Plug                                                                                                                                                                                                                                   |
| Material       | Nylon                                                                                                                                                                                                                                                  |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 20 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
|-----------------------|----------------------------------------------------------|

Product Assets

- [Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Catalog Page \[English\]](#)  
[Installation Manual \[Spanish, French, English\]](#)