

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, L5-20R, Screw Terminal, White

By Hubbell Wiring Device-Kellems
Catalog # [HBL2310M5](#)

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, L5-20R, Screw Terminal, White

Features

- High-impact, abuse-resistant nylon face
- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems

Application

Heavy Duty Industrial

Specifications

Nema Rating	L5-20R
Industry Standard(s)	WR Rating
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire Grounding
Wire Size	#12 AWG to #10 AWG



Current

Amperage Rating	20 A
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A
Current Rating	20 A

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color	White
UPC	783585238265
Material - Mounting Hardware	Screw Mounting
Item Type	Single
Material	Thermoplastic

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[Spanish\]](#)