

Locking Devices, Twist-Lock®, Valise, Male Plug, 20A 125V, 2-Pole 3-Wire Grounding, L5-20P, Screw Terminal, Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL2311VBK](#)

Locking Devices, Twist-Lock®, Valise, Male Plug, 20A 125V, 2-Pole 3-Wire Grounding, L5-20P, Screw Terminal, Black

Features

- One piece all-black body design uses less fasteners for ease of assembly
- Powerful cord grip prevents conductor slippage and strain on wiring terminals
- Totally insulated impact and crush resistant nylon body
- Unique patented clamp type terminals provide a superior electrical connection by bundling the conductor strands when clamps are tightened

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Environmental - Terminal Identification - Terminals identified in accordance with UL 498, Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only.

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Nema Rating	L5-20P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole
Cable Range	0.325 - 0.720 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------



Current

Amperage Rating	20 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 VAC
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	1.78 in
Display Size	Standard Sized
Weight	0.20 lb.
Height	2.50 in
Width	1.78 in
Dimensions	1.78 in x 1.78 in x 2.50 in

General

Color	Black
Cord Range	0.325"-0.720"(8.26-18.3)
Specifications	• Blades - Brass • Clamp Screws - #8 - 32 Steel - Zinc plated (Philips / Slotted / Robertson) • Housing - Black nylon • Terminal Clamps - Steel - Nickel plated • Terminal Screws - #8 - 32 Steel (Philips / Slotted / Robertson)
UPC	783585043005
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	20A Valise® Plug
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand