

Locking Devices, Twist-Lock®, Valise,
Female Connector Body, 20A 125V, 2-Pole
3-Wire Grounding, L5-20R, Screw Terminal,
Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL2313VBK](#)

Locking Devices, Twist-Lock®, Valise, Female Connector Body,
20A 125V, 2-Pole 3-Wire Grounding, L5-20R, Screw Terminal,
Black

Features

- Unique patented clamp type terminals provide a superior electrical connection by “bundling” the conductor strands when clamps are tightened
- Totally insulated impact and crush resistant nylon body
- Powerful cord grip prevents conductor slippage and strain on wiring terminals

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for full rated current,
Electrical - Dielectric Voltage - Withstands 2,000V minimum,
Environmental - Flammability - HB or better per UL 94 or CSA
22.2 No. 0.6, Environmental - Moisture Resistance - IP20
Suitability, Environmental - Operating Temperature - Maximum
continuous 75°C, minimum -40°C (w/o impact), Mechanical -
Terminal Accommodation - #14 AWG- #8 AWG stranded copper
wire only., Mechanical - Terminal Identification - Terminals
identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L5-20R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #8 AWG
Number Of Poles	2-Pole
Cable Range	0.325 - 0.720 in

Current



Amperage Rating	20 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	20 A

Dimensions

Length	1.81 in
Display Size	Standard
Weight	0.25 lb.
Height	3.5 in
Width	1.81 in
Dimensions	1.81 in x 1.81 in x 3.5 in

General

Color	Black
Cord Range	0.325"-0.720"(8.26-18.3)
Specifications	• Clamp Screws - #8 - 32 Steel - Zinc plated (Philips / Slotted / Robertson) • Contacts - Brass • Housing - Black nylon • Terminal Clamps - Steel - Nickel plated • Terminal Screws - #8 - 32 Steel (Philips / Slotted / Robertson)
UPC	783585043029
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	20A Valise® Connector
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C
Horsepower - Maximum	1

Operating Temperature

- Minimum Continuous: -40° C w/o impact, -25° with impact
Maximum continuous 75° C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand