

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, 20A 480V
AC, NEMA L8-20R, Watertight Safety-
Shroud® Valox® housing and flange.**

By Hubbell Wiring Device-Kellems

Catalog # [HBL2340SW](#)

Locking Devices, Twist-Lock®, 20A 480V AC, 2-Pole 3-Wire
Grounding, NEMA L8-20R, Watertight Safety-Shroud®, gray
Valox® housing and flange, back and side wired.



Features

- High impact, thermoplastic housing for heavy-duty industrial environments
- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use

Application

Heavy Duty Industrial Shrouded Watertight

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - VO per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - Type 4, 4X, 12, IP66 suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications


Environmental Conditions	Watertight
EU RoHS Indicator	Yes
Nema Rating	L8-20R
Industry Standard(s)	UL Listed, CSA Certified To Type 4, 4X And Type 12

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	480 VAC
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A



Dimensions

Length	3.75 in
Display Size	Standard Sized Product
Height	2.6 in
Width	3.75 in
Dimensions	3.75 in x 3.75 in x 2.6 in

General

Color	Gray
Specifications	• Body Contact Carrier - Natural (white) nylon • Contacts - Brass • Drive Screws - Steel, zinc plated • Housing / Cover - Gray RPT • Lift-Cover Spring & Pin - Stainless Steel • Terminal Retainer - Clear polycarbonate
Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42 • UL Listed • CSA Certified to Type 4, 4X and Type 12
UPC	783585313146
Material - Mounting Hardware Item Type	Screw Mounting 20A Watertight Safety-Shroud® Receptacle
Material	Thermoplastic

Logistics

Carton Quantity	5
-----------------	---

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish\]](#)