

Locking Devices, Twist-Lock®, Corrosion
Resistant Insulgrip® Connector, 20A, 250V
AC, 2 Pole, 3 Wire Grounding, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL23CM23](#)

Locking Devices, Twist-Lock®, Corrosion Resistant Insulgrip®
Connector, 20A, 250V AC, 2 Pole, 3 Wire Grounding, Yellow

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Integral dust shield protects wiring chamber from dust or contaminants

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-20R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A



Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	20 A

Dimensions

Length	3.86 in
Display Size	Standard
Weight	0.30 lb.
Height	2.26 in
Width	2.26 in
Dimensions	3.86 in x 2.26 in x 2.26 in

General

Color	Yellow
Cord Range	0.360"-0.930" (9-24)
Specifications	• Assembly Screws - Steel - nickel plated • Contacts - Nickel Plated Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Bronze (Phillips / Slotted / Robertson)
UPC	783585038124
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	Corrosion Resistant Insulgrip® Connector
Material	Nylon

Logistics

Carton Quantity	30
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
--------------------	--

Operating Temperature

Maximum continuous 75°C and
minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish\]](#)



A Hubbell brand