

Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 20A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-20P, Screw Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL24CM21](#)

Twist-Lock® Marine Grade, Male Plug 20A L15

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Integral dust shield protects wiring chamber from dust or contaminants

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L15-20P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	3-Pole
Cable Range	0.350 - 1.150 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------



Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Phase	Three Phase
Current / Amperage Rating	20 A

Dimensions

Length	2.33 in
Display Size	Standard Sized
Weight	0.35 lb.
Height	2.75 in
Width	2.33 in
Dimensions	2.33 in x 2.33 in x 2.75 in

General

Color	Yellow
Cord Range	0.350"-1.150" (9-29)
Specifications	• Assembly Screws - Stainless Steel • Blades - Nickel Plated Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Bronze (Phillips / Slotted / Robertson)
UPC	783585038490
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	20A Corrosion Resistant Insulgrip® Plug
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	3

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [French, English]



A Hubbell brand