

Locking Devices, Twist-Lock®, Elastogrip,
Male Plug, 15A 125V, 2-Pole 3-Wire
Grounding, L5-15P, Screw Terminal, Yellow,
Water/Dust-Tight Housing

By Hubbell Wiring Device-Kellems
Catalog # [HBL24W47](#)

Locking Devices, Twist-Lock®, Elastogrip, Male Plug, 15A 125V, 2-
Pole 3-Wire Grounding, L5-15P, Screw Terminal, Yellow,
Water/Dust-Tight Housing

Features

- Integral weatherproofing shroud seals connection between plug and connector
- Nylon compression nut keeps water and dust from getting into the body around the cord

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG- #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Watertight
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L5-15P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole
Cable Range	0.300 - 0.655 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current



Amperage Rating	15 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 VAC
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.55 in
Display Size	Standard Sized
Weight	0.20 lb.
Height	2.65 in
Width	1.55 in
Dimensions	1.55 in x 1.55 in x 2.65 in

General

Color	Yellow
Cord Range	0.300"- .655"(7.6-16.6)
Specifications	• Assembly Screws - Steel, zinc plated • Blades - Brass • Strain Relief Nut - Nylon • Terminal Retainer - Clear polycarbonate • Terminal Screws - Brass
UPC	783585235844
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Grounding Elastogrip® Plug
Material	Elastomer / Elastomeric

Logistics

Pallet Quantity	4050
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand