

Locking Devices, Hubbellock, Industrial,
Receptacle, 30A 600V AC, 20A 250V DC,
4-Pole 5-Wire Grounding, Non NEMA,
Screw Terminal, Blue.

By Hubbell Wiring Device-Kellems
Catalog # [HBL25403](#)



Hubbellock Industrial Receptacle 30A 20A DC, Non NEMA

Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Metallic housing provides protection from damage in harsh environments

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0 for Receptacles and Inlets.HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #10 AWG - #6 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	5-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	4-Pole

Current

Amperage Rating	20/30 A
-----------------	---------

Voltage Rating Description	250 VDC/600 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VDC/600 VAC
Connectivity	Back Wired Screw Terminals
Current / Amperage Rating	20/30 A

Dimensions

Length	4.56 in
Display Size	Standard Sized Product
Weight	0.95 lb.
Height	2.94 in
Width	2.84 in
Dimensions	4.56 in x 2.84 in x 2.94 in

General

Specifications	• Contacts - Brass • Housing - Cast aluminum • Receptacle Interior - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017464
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	20A/30A Grounding Hubbellock® Receptacle
Material	Aluminum, Cast

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)