

Locking Devices, Hubbellock, Industrial,
Steel Shroud, Male Plug, 30A 600V AC,
20A 250V DC, 4-Pole 5-Wire Grounding,
Non NEMA, Screw Terminal/White

By Hubbell Wiring Device-Kellems
Catalog # [HBL25415B](#)

Locking Devices, Hubbellock, Industrial, Steel Shroud, Male Plug,
30A 600V AC, 20A 250V DC, 4-Pole 5-Wire Grounding, Non
NEMA, Screw Terminal, Black/White

Features

- Molded-in male contacts are resistant to damage and provide a consistently positive connection
- Insulated non-metallic housing enhances safety and abuse resistance
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Three-piece clamp assembly provides maximum strain relief and protects against entry of moisture and dust

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage Withstand - 2,000V minimum, Environmental - Flammability - UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #10 AWG - #6 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	5-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	4-Pole
Cable Range	0.700 - 1.200 in

Current

Amperage Rating	20/30 A
Voltage Rating Description	250 VDC/600 VAC
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	250 VDC/600 VAC



Current / Amperage Rating	20/30 A
---------------------------	---------

Dimensions

Length	2.5 in
Weight	1.4 lb.
Height	6.56 in
Width	2.5 in
Dimensions	2.5 in x 2.5 in x 6.56 in

General

Color	Black, White
Cord Range	0.760"-1.200" (19.30-30.4)
Specifications	• Assembly Screws - Stainless Steel • Contacts - Brass • Cord Clamp Material - PET • Device Color - Black/White • Housing - Nylon • Plug Housing - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017488
Type	Plugs
Item Type	20A/30A Hubbellock® Plug
Material	Nylon

Logistics

Pallet Quantity	910
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)