

Locking Devices, Twist-Lock®, Elastogrip,
Female Connector Body, 15A 125V, 2-Pole
3-Wire Grounding, L5-15R, Screw Terminal,
Water/Dust-Tight Housing

By Hubbell Wiring Device-Kellems
Catalog # [HBL25W47](#)

Locking Devices, Twist-Lock®, Elastogrip, Female Connector
Body, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal,
Yellow, Water/Dust-Tight Housing

Features

- Integral weatherproofing shroud seals connection between plug and connector
- Nylon compression nut keeps water and dust from getting into the body around the cord

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG- #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	No
Nema Rating	L6-15R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole
Cable Range	0.300 - 0.655 in

Current

Amperage Rating	15 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 VAC



Connectivity	Pressure Terminal Screws
Current / Amperage Rating	15 A
Dimensions	
Length	1.76 in
Display Size	Standard
Weight	0.35 lb.
Height	4.03 in
Width	1.76 in
Dimensions	1.76 in x 1.76 in x 4.03 in
General	
Color	Yellow
Cord Range	0.300"- .655"(7.6-16.6)
Specifications	• Assembly Screws - Steel, zinc plated • Contacts - Brass • Strain Relief Nut - Nylon • Terminal Retainer - Clear polycarbonate • Terminal Screws - Brass
UPC	783585235912
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	15A Grounding Elastogrip® Connector
Material	Elastomer / Elastomeric
Logistics	
Pallet Quantity	1200
Carton Quantity	10
Operational	
Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand