

Locking Devices, Twist-Lock®, Single Flush Receptacle, 30A, 2 Pole, 3 Wire, 240VAC, Line to Neutral, NEMA L25-30R nylon face, back and side wired

By Hubbell Wiring Device-Kellems
Catalog # [HBL2600](#)

Locking Devices, Twist-Lock®, Single Flush Receptacle, 30A, 2 Pole, 3 Wire, 240VAC, Line to Neutral, NEMA L25-30R, Black nylon face, back and side wired

Features

- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems

Performance

Electrical-Current Interrupting - Certified at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Mechanical - Terminal Accommodation - #16 - #8 AWG stranded, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance	CM
Status	
Industry Standard(s)	WR Rating
EU RoHS Indicator	Contact Manufacturer



Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Dimensions

Height	1.31 in
Length	3.28 in

General

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585580319
Item Type	30A Single Flush Receptacle

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish\]](#)