

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 2 Pole, 3 Wire, 240VAC, Line to Neutral, NEMA L25-30P, Black and White Nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2601](#)

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 2 Pole, 3 Wire, 240VAC, Line to Neutral, NEMA L25-30P, Black and White Nylon

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Clear, funnel shaped wire entry for ease of termination
- Integral, dust shield protects wiring chamber from dust or contaminants

Performance

Electrical-Current Interrupting - Certified at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Mechanical - Terminal Accommodation - #16 - #8 AWG stranded, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer



Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Dimensions

Height	2.75 in
Length	1.92 in

General

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585580289
Item Type	30A Insulgrip® Plug

Logistics

Carton Quantity	30
-----------------	----

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish\]](#)