

Locking Devices, Twist-Lock®, Insulgrip®
Inlet, 30A, 2 Pole, 3 Wire, 240VAC, Line to
Neutral, NEMA L25-30P, Back Wired, White
Nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2605](#)

Locking Devices, Twist-Lock®, Insulgrip® Inlet, 30A, 2 Pole, 3 Wire,
240VAC, Line to Neutral, NEMA L25-30P, Back Wired, White
Nylon

Features

- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Performance

Electrical-Current Interrupting - Certified at full rated current,
Electrical - Dielectric Voltage - 2,000V minimum, Mechanical -
Terminal Accommodation - #16 - #8 AWG stranded, Mechanical -
Terminal Identification - Terminals identified in accordance with
UL 498, Environmental - Flammability - HB or better per
UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance -
IP20 Suitability, Environmental - Operating Temperatures -
Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer

Conductor



Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Dimensions

Height	2.09 in
Length	2.88 in

General

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585580302
Item Type	30A Insulgrip® Inlet

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French\]](#)