

HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Connector Body, Reversed Service, Industrial Grade, 30A 125V, 2-Pole 3-Wire Grounding, L5-30P, White

By Hubbell Wiring Device-Kellems
Catalog # [HBL2613SR](#)

Locking Devices, Twist-Lock®, Connector Body, Reversed Service,
Industrial Grade, 30A 125V, 2-Pole 3-Wire Grounding, L5-30P,
White



Features

- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Superior cord grip design protects terminations from excess strain
- UL Type 4X Environmental seal protects connection while in use.

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L5-30R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole
Cable Range	0.350 - 1.150 in

Current

Amperage Rating	30 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A

Voltage Rating	125 VAC
Current / Amperage Rating	30 A

Dimensions

Length	2.94 in
Height	5.5 in
Width	2.94 in
Dimensions	2.94 in x 2.94 in x 5.5 in

General

Specifications	• Assembly Screws - Stainless Steel • Contacts - Brass • Housing / Cord Clamp - PBT • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson) • Watertight Gland - Neoprene
UPC	783585458090
Type	Connector Body
Item Type	30A Watertight Safety-Shroud® Reverse Service Connector

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)

